

3P Surface Area and Porosity Analyzers



- BET Surface Area
- Pore Size Distribution
- Pore Volume

- Adsorption Capacity
- Chemisorption Parameters
- Vapor Sorption

- Heat of Adsorption
- Research and Development
- Quality Control

STATIC-VOLUMETRIC AND DYNAMIC GAS ADSORPTION ANALYZERS

PARTICLE CHARACTERIZATION

POWDER ANALYSIS

PORE DETERMINATION



Characterization of
particles • powders • pores

info@3p-instruments.com
www.3p-instruments.com

Contents

Overview 2

3P micro series 4

Up to three independent analysis ports for high-performance physical adsorption experiments of microporous materials, such as active carbon, zeolites, MOFs, etc



3P meso series 7

Up to four independent analysis ports for the determination of meso and macro pores from 2 up to 500 nm



3P sync series 10

Sorption analyzer with up to four measuring stations in one dewar: high sample throughput with small lab space requirement, combined with minimum liquid nitrogen consumption



3P surface DX 13

Fully automated dynamic single- and multi-point sorption analyzer with reference mode for fast BET measurements



Optional Accessories and Tools 15

External degasser, additional vapor source, cryostatic accessories and our simulation software for dynamic experiments or mixed gas experiments



MixSorb series 17

For mixed gas/vapor adsorption




Applications

- Research and Development
- Quality Control
- Zeolites, MOFs, active carbon, silica gels, ...
- Determination of BET surface area
- Analysis of Pore Size Distribution and Pore Volume
- Determination of Chemisorption Parameters
- Vapor Sorption Measurements
- Determination of Adsorption Capacity and Heat of Adsorption

Introduction

For 30 years, 3P Instruments has been standing for methods of the characterization of particles, powders and porous materials in Europe. The purpose of the department "Surfaces & Pores" is to offer professional consultation and scientific solutions concerning our analytical instruments and methods to customers in the fields of research, development, or quality control of powders and porous materials. We are mainly




focused on the determination and evaluation of characteristics such as the BET surface area, pore size distribution, porosity, pore volume, adsorption capacity, chemisorption parameters, breakthrough analysis, mixed gas adsorption, density, and permeability.




3P Gas Adsorption Analyzer Series


The characterization of surface areas and pores of solid materials are important parameters in many laboratories and are usually determined by gas adsorption equipment. These techniques can be complemented by adsorption of water and other vapors, chemisorption, high-pressure- and breakthrough measurements. 3P Instruments offers a broad range of different surface area and pore size analyzers, perfectly designed to meet your application requirements in terms of



analysis parameters, flexibility, desired sample throughput, ease of use and analysis speed. This brochure gives an overview of our instrument models and possible configurations.



Example: Mesopore Analysis



Example: Micropore Analysis

3P sync series



With the 3P sync series, 3P Instruments now offers new measuring instruments with up to four measuring stations and a separate p_0 measuring cell for simultaneous measurement of the saturation vapor pressure. The stations and measuring cells are temperature-controlled by one Dewar. Thus, the 3P sync enables the highest sample throughput with the smallest possible space requirement and minimum liquid nitrogen consumption. Depending on the sample volume, it can be equipped individually as a 1-, 2-, 3- or 4-station instrument. In addition, the number of pressure transducers can be configured at the measuring station. If the instrument is to be equipped with the fastest possible measuring configuration, a separate pressure sensor can be integrated in each of the four measuring stations. If the measuring speed is not relevant (e.g., for measurements overnight), the measuring instrument can be equipped with only one pressure sensor for up to four measuring stations. Depending on the price/performance ratio, less than six pressure sensors can be integrated, resulting in seven different 3P sync model configurations.

Applicable methods and determinable parameters

- Isothermal adsorption and desorption curve
- BET specific surface area (single point, multi-point)
- Langmuir surface area
- External surface area (STSA)
- BJH pore size analysis
- t-plot analysis
- DR, DA, MP method
- HK pore size analysis
- SF pore size analysis
- NLDFT pore size distribution
- Pore size mode, average pore size, total pore volume
- Calculation of heat of adsorption, etc.

Benefits and Features

- The 3P sync series is available with up to four **measurement station(s)** for high resolution sorption measurement(s).
- **Three step evacuation routine** for safe sample handling including very fine particles and highly porous materials (Figure 1).
- Each measurement station has **its own pressure transducer** (optional) and each includes its own 1000 Torr p_0 transducer (Figure 2).
- Presentation of **real-time kinetic data (pressure versus time)** to check and visualize equilibrium conditions (Figure 3).
- **Two step filter system** to protect the system against sample contamination.
- Change of dose amounts and equilibration settings **on-the-fly**, a restart of the analysis is not necessary (Figure 4).




Figure 1




Figure 2





Figure 3



	Phase 1	Phase 2	Phase 3	Phase 4
Dose amount (mL/g)	4	2	1.5	3
Relative range (p/p_0)	0.01	0.4	0.8	0.998

Figure 4

Specifications

Model	440	420	330	310	220	210	110
Test Principle	Gas adsorption by static volumetric method						
Adsorbates	N ₂ , Ar, Kr, H ₂ , O ₂ , CO ₂ , CO, NH ₃ , CH ₄ , etc.						
Analysis ports	4	4	3	3	2	2	1
Analysis pressure transducers	5	3	4	2	3	2	2
p_0 Transducer	1	1	1	1	1	1	1
Surface Area Range	0.0005 m ² /g to unknown upper limit; Standard sample repeat accuracy $\leq \pm 1.0\%$						
Pore Size Range	0.35 nm – 500 nm						
Minimum Pore Volume	0.0001 cm ³ /g						
Pressure Sensor Accuracy	$\pm 0.15\%$ (Full Scale)						
Range of Relative Pressure p/p_0	10^{-4} – 0.998						
Vacuum System	Mechanical vacuum pump (ultimate vacuum 6.7×10^{-2} Pa)						
Dimensions	L 500 x W 500 x H 800 mm						
Weight	ca. 60 kg						
Temperature Requirements of Environment	15 – 40 °C						
Humidity Requirements of Environment	10 % – 90 %						
Power Requirements	AC 220 V $\pm$ 20 V, 50/60 Hz, maximum power 300 W, current 5 A						

Optional Accessories and Tools

Optional Accessories and Tools	3P micro	3P meso	3P sync
3P prep J4: Additional sample preparation system with 4 stations and a max. degasser temperature of 400°C. It offers an optional turbo vacuum and temperature ramp control (<i>Figure 1</i>).	■	■	■
Vapor source with heated manifold up to 50 °C (<i>Figure 2</i>).	■		
Tempering Kit for experiments from 0 to 50°C. It is most commonly used for CO ₂ , n-Butane or vapor experiments (<i>Figure 3</i>).	■	■	■
cryoTune series: Cryostatic accessory/temperature controller for adsorption using various adsorptives at temperatures 77–323 K. It needs only liquid nitrogen for cooling. It allows the characterization of microporous solids according to ISO 9277 and IUPAC 2015 recommendation, but also the determination of BET surface of other materials by Ar/Kr instead of N ₂ adsorption. It operates noiseless and has a very low energy consumption (<i>Figure 4</i>).	■	■	■
cryoCooler: Can be used for cryogen free temperature control for measurement temperatures < 20–320 K (<i>Figure 5</i>).	■		
Simulation software 3P sim to predict the performance of dynamic experiments or mixed gas experiments (<i>Figure 6, right page</i>).	■	■	■



Figure 1




Figure 2



Figure 3




Figure 4



Figure 5

Figure 6



Isotherm Fitting

With **3P sim** measured isotherm data can be fitted with the following mathematical isotherm models:

- HENRY
- LANGMUIR
- TOTH
- SIPS
- FREUNDLICH
- DUALSITE LANGMUIR
- DUALSITE LANGMUIR SIPS

Prediction of Mixture Equilibria

The program allows the calculation of total and partial loadings at given pressures or compositions and supports the following theories:

- IAST* with LANGMUIR
- IAST with TOTH
- IAST with DUALSITE LANGMUIR
- IAST with DUALS. LANGMUIR SIPS
- Multicomponent LANGMUIR
- Multicomponent SIPS

* Ideal Adsorption Solution Theory

Dynamic Simulation

- **3P sim** provides solutions for mass- and energy balances which allow simulations without user precognition or programming skills.
- Technically relevant transport parameters (e.g., LDF* constants) are accessible
- Simulation of breakthrough curves and temperature profiles

* Linear Driving Force

